

REQUEST FOR QUOTE / ORDERING INFORMATION

Rep Name _____
 Customer _____

Salesman _____
 Customer Contact _____

1 APPLICATION DATA

Process Fluid _____
 % Concentration _____
 Specific Gravity (at Operating Temp) _____
 Interface Specific Gravity _____ / _____
 Pressure Design / Operating _____ / _____
 Temp Design / Operating _____ / _____

2 FABRICATION DATA

Chamber Material _____
 Process Connection Material _____
 Vent / Drain Connection Material _____
 Process Connection Size _____ Rating _____
 Flange _____ / _____
 Coupling _____ / _____
 Nipple _____ / _____
 Gussets Yes Support Bracket Yes
 Vent / Drain Valves (Ball, Gate, Plug, and Mfg) _____

3 INDICATION DATA

Inches of Visual Indication _____
 Inches of Center to Center _____
 Indicator : Standard Flashing

 Special Scale (Describe : Provide Drawing)

 Glass Tube Protector: Yes

4 INSULATION

Blanket Cryogenic
 Indicator Non-Frosting Protection :
 Steam Electric

5 HEAT TRACING

Steam Electric
 Reason for Heat Tracing:
 Freeze Protection
 Maintaining Process Temperature

6 SWITCHES

Electrical _____ Part # _____
 ES-21
 ES-30EX
 ES-40
 Hazardous Classification _____

Pneumatic _____ Block / Bleed _____
 AS-35 Rising Level
 AS-50 Falling Level
 Supply Gas _____

Clamp Mount Rod Mount Pad Mount (above 200 deg F)

7 OTHER OPTIONS

CLT (Remote Transmitter) _____
 Controllers _____
 Indicators _____

Provide Sketch

Questions and / or Notations

- (1) Are there any obstructions that will limit our dimensions on this PM-26 ?
- (2) Orientation of Scale Kit ?
- (3) Orientation of Process Connections ?
- (4) Will you have enough clearance to remove the float from the bottom of the PM-26 Chamber ? Note: Lower Specific Gravities may require a longer dead leg.

Part # **PM26-** _____

Refer to pages 12, 13, 14, and 15 to determine correct part number.